



# GRITTGEAR®

## Technical Data Explaining Technical Drawing

Description	Material Composition	Dimensions	Method of Assembly
1. Toe Cap	Steel	Thickness: 2mm Length: 34mm - 42mm	Setting and bonding
2. Collar Lining	Fabric	Weight: 130g/m	Glue and stitching
3. Label Inside Tongue (with NRCS marking)	Synthetic fabric	Length: 4.0cm Width: 3.5cm	Stitching
4. Elastic Strip	Elastic	Width: 2.5-4.5cm	Stitching
5. Midsole	Polyurathane	Min thickness: 2.5cm	Injection moulded
6. Eyelets	/	/	/
7. Upper	Cow Crazy Horse Leather	Thickness: 1.8mm-2.0mm	Stitching
8. Insole	Mesh + Foam + EVA	Thickness: 8mm	Manual insertion, non-bound
9. Outsole	Rubber	Length: 277.3 mm - 335.8mm	Injection moulded
10. Vamp Lining	Non-woven fabric	Thickness: 1.5mm	Glue and stitching
11. Cleats	Rubber	Min height: 4mm	Injection moulded
12. Penetration Insert	Kevlar	Thickness: 4mm	/



1  
(not to scale)



8  
(not to scale)



9

11