



a) The following component parts, a description of each component part, and material/s used in each component part:

i. Upper;	Smooth cow leather																						
ii. Insole (when used);	Polyester non-woven																						
iii. Insock (when used);	Black Mesh + EVA with antistatic thread																						
iv. Outsole;	PU/PU																						
v. Toecap;	Steel																						
vi. Vamp lining;	Non-woven fabric																						
vii. Quarter lining;	Nylon mesh																						
viii. Edge covering of the toecap;	PVC																						
ix. Scuff resistant coverings for the toe region (when used);	N/A																						
x. Collar and insert materials above the upper (when fitted);	N/A																						
xi. Tongue;	N/A																						
xii. Penetration-resistant insert (when fitted);	N/A																						
xiii. Heat and/or cold insulation (when fitted);	N/A																						
xiv. Metatarsal protective device (when fitted);	N/A																						
xv. Cut resistant layer (when fitted);	N/A																						
b) Upper:																							
i. Height of the upper;	<table border="1"> <tbody> <tr><td>3 - 4</td><td>132mm</td></tr> <tr><td>5 - 6</td><td>140mm</td></tr> <tr><td>7 - 8</td><td>147mm</td></tr> <tr><td>9 - 10</td><td>152mm</td></tr> <tr><td>11 - 12</td><td>157mm</td></tr> <tr><td>13</td><td>162mm</td></tr> </tbody> </table>	3 - 4	132mm	5 - 6	140mm	7 - 8	147mm	9 - 10	152mm	11 - 12	157mm	13	162mm										
3 - 4	132mm																						
5 - 6	140mm																						
7 - 8	147mm																						
9 - 10	152mm																						
11 - 12	157mm																						
13	162mm																						
ii. Thickness of the materials used in the upper;	1,6mm																						
c) Layout of the seat region;																							
Closed seat region																							
d) Insole (when used):																							
i. Thickness of the insole;	2mm for all sizes																						
ii. Method of assembly of the insole to the footwear;	Subject to heat and pressure between heated platens																						
e) Type of insock (when used):																							
i. Non-removable insock, OR;	N/A																						
ii. Seat sock, OR;	N/A																						
iii. Full insock, non-removable, OR;	N/A																						
iv. Full insock, removable and water permeable, OR;	X - Full insock, removable and water permeable,																						
v. Full insock, removable, not water permeable;																							
f) Thickness of the insock (when used);	6-8mm for all sizes																						
g) Method of assembly of a non-removable insock to the footwear (when used);	Manual insertion, non-bound																						
h) Toecap:																							
i. Method of assembly of the toecap to the footwear;	Setting and bonding																						
ii. Internal length of the toecap;	<table border="1"> <tbody> <tr><td>3 - 4</td><td>34mm</td></tr> <tr><td>5 - 6</td><td>36mm</td></tr> <tr><td>7 - 8</td><td>38mm</td></tr> <tr><td>9 - 10</td><td>39mm</td></tr> <tr><td>11 - 12</td><td>40mm</td></tr> <tr><td>13</td><td>42mm</td></tr> </tbody> </table>	3 - 4	34mm	5 - 6	36mm	7 - 8	38mm	9 - 10	39mm	11 - 12	40mm	13	42mm										
3 - 4	34mm																						
5 - 6	36mm																						
7 - 8	38mm																						
9 - 10	39mm																						
11 - 12	40mm																						
13	42mm																						
iii. Minimum thickness of the material used in the toecap;	2mm for all sizes																						
i) The position and all dimensions (including the thickness of the material used) of an edge covering under the back edge of the toecap;	<table border="1"> <tbody> <tr><td>3</td><td>5</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td></tr> <tr><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td></tr> </tbody> </table>	3	5	5	6	7	8	9	10	11	12	13	15	15	15	15	15	15	15	15	15	15	15
3	5	5	6	7	8	9	10	11	12	13													
15	15	15	15	15	15	15	15	15	15	15													
Edge cover beneath the toecap	<table border="1"> <tbody> <tr><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td><td>10</td></tr> </tbody> </table>	10	10	10	10	10	10	10	10	10	10	10											
10	10	10	10	10	10	10	10	10	10	10													

j) Thickness of the scuff resistant coverings for the toe region;	3	4	5	6	7	8	9	10	11	12	13
	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3

k) Outsole:

- i. Method of assembly of the outsole to the upper;
- ii. Minimum thickness of the outsole (excluding cleats and heel);
- iii. Cleat pattern (when used);

Injection

2.5mm for all sizes



iv. Length of the outsole;

3	265.00mm
4	271.04mm
5	277.04mm
6	283.72mm
7	290.04mm
8	297.08mm
9	303.76mm
10	310.44mm
11	317.12mm
12	323.0mm
13	330.48mm

v. Minimum cleat height (when used);

6.6mm for all sizes

l) For outsoles that consist of more than one layer:

- i. Number of layers;
- ii. Material used in each layer;
- iii. Minimum thickness of each layer;
- iv. Method of assembly of the different layers to each other;
- i. Thickness of the penetration-resistant insert;
- ii. Method of assembly and layout of the penetration-resistant insert in the footwear;

2

PU/PU

4-6mm

Injection

N/A

N/A

Not applicable

n) Heat and/or cold insulation (when fitted):

- i. Thickness of the heat and/or cold insulation;
- ii. Method of assembly of the heat and/or cold insulation to the footwear;
- i. Thickness of the metatarsal protective device;

Not applicable

Not applicable

Not applicable

- ii. Method of assembly of the metatarsal protective device to the footwear;

Not applicable

Not applicable

p) Cut resistant layer (when fitted):

- iii. Thickness of the cut resistant layer;
- iv. Minimum height of the cut resistant layer above the feather edge;
- v. The minimum measurement of overlap of the cut resistant layer beyond the rear end of the toecap;
- vi. Method of assembly of the cut resistant layer to the footwear.

Not applicable

Not applicable

Not applicable

Not applicable